

9651PD Wired 8 zone control panel



The new 9651PD from Scantronic brings this hugely popular product right up to date with PD6662:2010 at grade 2X. The new design has enabled a reduction in the panel power consumption by an amazing 70%.

Also Available

9651UK-41

Simple non-compliant panel for ungraded installations.

9651EN-41 and 9651EN-43

Remains available for retro-fit installations and servicing.

At a glance...

- 350 event log (250 mandatory events and up to 100 non-mandatory events), which is date and time stamped
- Compliant to PD6662:2010 at Grade 2x
- Simplified user interface and installer menus



Powering Business Worldwide

Product specification

Compliance	PD6662:2010, EN50131-1:2006 + A1:2009 Grade 2X and environmental class II, EN50131-3:2009, EN50131-6:2008
Zones	8 FSL Zones or 8 CC with global tamper
Panel	09651PD-41: Supplied with 09941EN non prox keypad. 09651PD-43: Supplied with 09943EN prox keypad
Keypads	Accepts up to four wired keypads
Proximity Reader	09943EN keypad has a built-in prox reader
Display	2 x 16 character LCD display
Setting Options	Full set and 3 parts sets
Event Log	350 Events
Codes	50 User codes can be 4 digit pin or proximity tag
Internal Sounder	Supports 1 x 16 Ω speaker
Outputs	3 programmable outputs
Remote Communications	None built in, can connect speech diallers from the SD range
Power Supply	Conforms to EN50131-6:2008 type A power supply. Rated output of 1A of which 800mA is available for system power
Battery	Accepts a 12V standby battery up to 7Ah rechargeable lead acid gel type
Dimensions	240 x 250 x 90 mm HxWxD (Panel)
Weight	2.85 kg (without standby battery) (Panel)
Temperature Range	Environmental class II (-10°C to 55°C @ 75% RH)

Compatible products

09651PD-41	8 zone, grade 2X control panel supplied with a 09941EN-41 non prox keypad
09651PD-43	8 zone, grade 2X control panel supplied with a 09941EN-43 prox keypad
09941EN	Keypad with a 16 x 2 line LCD display
09943EN	Keypad with a 16 x 2 line LCD display. Also has a built in proximity reader
SD1-UK	PSTN Speech dialler
TSD2-UK	PSTN Speech dialler with SMS
SD3	GSM / PSTN Speech dialler
SD-GSM	GSM Speech dialler

Features, Options & Technical Specifications are subject to change and alteration without prior notification.



Eaton
Electrical Sector EMEA
Route de la Longeraie 7
1110 Morges, Switzerland

Eaton
Security House,
Vantage Point Business Village,
Mitcheldean, Gloucestershire
GL17 0SX

Tel: +44 (0)1594 545 400
Fax: +44 (0)1594 545 401
Email: securitysales@eaton.com
Web: www.touchpoint-online.com